Fujitsu recommends Windows 7.

FUJITSU

Data Sheet

Fujitsu ESPRIMO P900 premium selection Desktop PC

First Class Computing

The Fujitsu ESPRIMO P900 premium selection micro-tower provides you high-end PC performance with 2nd gen Intel® Core™ i5 vPro™ processing, NVIDIA® GeForce® graphics, and lots of RAM. Get working fast with the Fujitsu Premium Suite software package. The 92% efficient power supply will reduce your energy bills. Ergonomic working is ensured thanks to the DisplayPort to DVI cable for easy working on a second monitor and an elegant spill-resistant keyboard with stylish mouse.

Microtower

Maximum performance and optimal extendability

- Top-quality, high-value microtower, 7 drive bays, 4 PCI/PCI express interfaces
- Elegant spill-resistant KB900 keyboard and stylish GL9000 laser mouse

Environmentally conscious product with ENERGY STAR® certification

Your contribution to environmental protection.

 Halogen-free printed circuit of mainboard and power supply, sophisticated product concept for the entire lifecycle

Highest energy efficiency coupled with intelligent performance

Low power consumption combined with top performance

State-of-the-art Intel® Core™ processors with Turbo Boost and hyperthreading technology, a switched monitor outlet and a power supply with up to 92% efficiency

System management

Simple system administration for complex IT infrastructures

Intel® vPro™ technology

Quiet

Pleasant working environment due to an extremely quiet system

■ Innovative hardware design, optimized cooling concept

































Components

Processor	Intel® Core™ i5-2500 processor (4 Cores / 4 Threads, 3.30 GHz, 6 MB, Intel® HD Graphics 2000)
Operating system	
Operating system	Genuine Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux Genuine Windows Vista® Genuine Windows® XP
Operating system notes	Buy Microsoft® Office 2010 to use the full-featured Office software on this PC. Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com
Memory modules	4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
Hard disk drives (internal)	SATA III, 7200 rpm, 1000 GB, 3.5-inch
Graphics add on cards	NVIDIA® GeForce® GT 420
 Drives	DVD Super Multi
blives	MultiCard Reader 20in1 USB 3.0 front con., 3.5-Inch
Interface add on cards/components (optional)	<u> </u>
	USB 3.0 PCIe x1
	Gigabit Ethernet PCle x1, DS
	eSATA Interface
Base unit	ESPRIMO P900 E90+
Mainboard	
Mainboard type	D3062
Formfactor	ATX
Chipset	Intel® Q67
Processor socket	LGA 1155
Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	32 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same. > 16 GB support with future memory modules
LAN	10/100/1000 MBit/s Intel® 82579 LM
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound
I/O controller on board	
Serial ATA total	6
thereof SATA III	2
thereof eSATA	2 (optional)

Page 2 / 7 http://ts.fujitsu.com/esprimo

I/O controller on board	
Controller functions	Serial ATA II (3 Gbit)
controller reflections	Serial ATA III (6 Gbit)
	NCQ
	AHCI
	Raid 1/0
Interfaces	
Audio: line-in	1
Audio: line-in / microphone	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	14
USB 3.0 total	optional
USB front	4
USB rear	8
USB internal	2
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality
Input device / components	
	Optical USB tilt wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse
	KBPC PX ECO
	Mouse M440 ECO
Drive bays	
Drive bays total	7
2.5-inch internal bays	1
3.5-inch internal bays	2
3.5-inch external bays	2
5.25-inch external bays	2
Slots	
PCI-Express 2.0 x16	1 x (312 mm) full height
PCI-Express 2.0 x4 (mech. x16)	1 x (312 mm) full height
PCI-Express x1	1 x (312 mm) full height
PCI (32-bit / 33 MHz)	1 x (170 mm) full height
Graphics on board	
Graphics brand name	Intel® HD Graphics or HD Graphics 2000 (depending on CPU)
Shared video memory	up to 1759 MB

Page 3 / 7 http://ts.fujitsu.com/esprimo

Craphics on board	
Graphics on board	103/ v 769 pivol
TFT resolution (VGA)	1024 x 768 pixel
	1280 x 1024 pixel 1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1600 x 1200 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel
(2.54)	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
	2560 x 1440 pixel
	2560 x 1600 pixel
Graphics features	Dual display support
	DirectX 10.1
	HDCP support
	OpenGL® 2.1
	For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 88% / 92% / 91%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	280 W
Power factor correction/active power	active
Monitor outlet	Switched
Power consumption	
Power consumption note	See white paper Energy Consumption
Link to Energy White Paper	http://docs.ts.fujitsu.com/dl.aspx?id=97001b4f-3df1-4981-8d8a-e863472c4769
Heat dissipation	
Heat dissipation notes	See white paper Energy Consumption
Noise for standard configuration (HDD)	
Noise emission	According to ISO9296
Related Processors for noise	Intel® Core™ i5 2400
Noise Operation mode 1: ODD load (Blue angel requirement)	4.0 B/ 26 dB(A)
Noise Operation mode 2: HDD load	3.5 B/ 20 dB(A)
(Blue angel requirement)	

Page 4 / 7 http://ts.fujitsu.com/esprimo

Noise for standard configuration (UDD)	ODD FDD)
Noise for standard configuration (HDD, Noise Operation mode 3: CPU 90% load	
(Blue angel requirement)	3.3 bi 20 db(n)
Noise Operation mode 4: High load	3.6 B/ 21 dB(A)
Idle mode (Blue Angel requirement)	3.4 B/ 19 dB(A)
Noise notes / description	A weighted sound power level Lwad (in B) / workplace related A-weighted sound pressure level LpAm (in dB(A)), Bystander position
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	175 x 419 x 395 mm
Operating position	Vertical
Weight	approx. 11 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35C
Compliance	
Product	ESPRIMO P900
Model	MI5W-3062
Germany	TÜV GS
Europe	CE
•	Nordic Swan
USA/Canada	FCC Class B
	cCSAus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronical equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® EPEAT® Gold (dedicated regions)
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx
Additional Software	
Additional software (preinstalled)	Nero 9 Essentials XL Premium Suite DVD Fujitsu Recovery (Hard Disk Based Recovery) Norton Internet Security (incl. Firewall) 60 days version Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics)
Miscellaneous	
	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime
Compatibility (references)	
1 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	DMI 2.0 PC 2001 WMI 1.5 USB 2.0 SMBIOS
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) iAMT 7.0

Page 5 / 7

Manageability	
Manageability software	DeskView 10.x client management including:
DeskView components	On/Offline remote client management
Desiries components	Detailed system inventory management and reports
	BIOS Management
	Remote power management
	System notifications
	Security Remote Control
	DeskView Helpdesk Integration
	WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability
	http://www.altiris.com/fujitsu
Security	
System protection	Kensington Lock support
	Eye for padlock
	Optional: Integrated cabinet lock
Audit proof protection	EraseDisk (optional)
	Boot sector virus protection
	Write protect option for the Flash EPROM
	Embedded security (TPM 1.2) Control of all USB interfaces
	External USB ports can be disabled separately Control of external interfaces
Access protection	User and supervisor BIOS password
Access protection	Hard disk password
	Optional: Access protection via external SmartCard reader
	Optional: Access protection via internal SmartCard reader
Serviceability	
Serviceability	EasyFix
	EasyChange for HDD
	EasyChange for optical drives
Packaging information	, , , , , , , , , , , , , , , , , , , ,
Packaging dimension	516x278x562 mm
Max. quantity / pallet	24
Material - Weight (g) Carton	1405 g
Material - Weight (g) EPS / PS	160 g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process
 Warranty	
Standard Warranty	3 years
Service level	Bring-In / On-Site Service (depending on country)
Maintenance and Support Services - tl	
Recommended Service	5x9, Response Time: Next Business Day
Coare Darte availability	5 years
Spare Parts availability	5 years



More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO P900 E90+, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO P900 E90+, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://ts.fujitsu.com/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at http://www.fujitsu.com/global/about/environment/



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu. com/terms_of_use.html Copyright Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU Technology Solutions Website: http://ts.fujitsu.com 2011-12-31 CE-EN All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright Fujitsu Technology Solutions